



TOUGHBOOK L1

- Android™ 8.1 (Oreo™)
- Optional integrated straight-shooting 1D/2D barcode reader configurable for landscape or portrait modes
- Industry standard quad-core processor by Qualcomm®
- Optional multi-carrier 4G LTE data support
- MIL-STD-810G, 5' Drop, All-weather IP65 and IP67 dust and water-resistant design
- 7" HD display with glove and rain mode
- 1 Year warranty with business class support
- Available with P.180 for seamless global connectivity

5-FOOT
DROP RATING

IP65

IP67

STYLISH, RUGGED AND CONFIGURABLE THIS PANASONIC TOUGHBOOK TABLET HAS PROFESSIONAL GRADE FEATURES AND ENTERPRISE CAPABILITIES

The Panasonic TOUGHBOOK L1 is a slim and sleek Android OS based 7" tablet that proudly carries the TOUGHBOOK name. Its ability to be used in the enterprise to collect information from workers in retail stores, warehouses, field service, transportation and delivery or many other environments where work must occur belies its mild looking exterior. The TOUGHBOOK L1 has a quad-core processor and an optional straight-shooting barcode reader that can be purchased in a portrait or landscape configuration, used with a stylus pen or connect to multi-carrier 4G LTE and provide the ease of use of the Android OS. Users of this handheld won't miss a beat with its great battery life, glove and rain touch enabled 7" screen, 5 foot drop rating and IP65 and IP67 certification. The TOUGHBOOK L1 is ready to be used by satisfied end users everywhere in your organization.

P.180
GET WORK DONE.™



800-373-5353
salesmanager@cdce.com
Business Hours: (PST) M-F 8:00 AM - 5:00 PM

TOUGHBOOK®

TOUGHBOOK L1

DURABILITY	<ul style="list-style-type: none"> Designed to meet MIL-STD-810G¹⁶ IP65 and IP67 sealed all-weather design 5' drop-resistant and tumble tested (500 tumbles, 3.3ft. 5 rpm)
SOFTWARE	<ul style="list-style-type: none"> Android 8.1 (Oreo)¹⁷
CPU	<ul style="list-style-type: none"> Qualcomm® MSM8909 1.1GHz Quad-Core
STORAGE & MEMORY	<ul style="list-style-type: none"> Memory 2GB¹ Storage eMMC: 16 GB¹ <ul style="list-style-type: none"> Additional storage available with optional Storage Card: SD (up to 2 GB), SDHC (up to 32 GB), SDXC (up to 64 GB)²
DISPLAY	<ul style="list-style-type: none"> 7" high definition 1280 x 720 10-point capacitive multi touch with rain sensing and glove touch modes <ul style="list-style-type: none"> Optional Passive Stylus Display with direct bonding Automatic screen rotation
AUDIO	<ul style="list-style-type: none"> Integrated microphone (x2) Loud volume mono speakers
KEYBOARD & INPUT	<ul style="list-style-type: none"> 10-point gloved multi touch 2 buttons (user-definable when using the BCR) On-screen QWERTY keyboard
SENSORS	<ul style="list-style-type: none"> Ambient light sensor and acceleration sensors
CAMERAS	<ul style="list-style-type: none"> Full HD 8MP rear camera with LED light
EXPANSION	<ul style="list-style-type: none"> microSDXC (up to 64 GB)²
INTERFACE	<ul style="list-style-type: none"> Docking connector Micro-USB option to be host or client interface 2.0 (x1)³ Mini-jack stereo headphone & microphone xPak interface
WIRELESS	<ul style="list-style-type: none"> Qualcomm® WCN3660B IEEE802.11 a/b/g/n/d/h/i/r Qualcomm® MSM8909 - 4G LTE, HSPA+, UMTS, EDGE, GPRS, GSM Certified with Verizon, AT&T and P.180 (Data only) Nano SIM card slot (x1) Bluetooth® v4.2 Classic Mode LE (class 1) GPS GPS/GLONASS CEP50 (±2 to 4 m) Near Field Communication (NFC) <ul style="list-style-type: none"> Type A, Type B, Felica
POWER SUPPLY ^{4,5,6,7,8,9,10,11}	<ul style="list-style-type: none"> Standard battery: Li-ion 3.8V, 3,200 mAh Standard battery operation <ul style="list-style-type: none"> Approx. 9 hours based on standard enterprise user profile⁹ Warm Swap Standard battery charging time: <ul style="list-style-type: none"> Power on or off approx. 2.5 hours⁴ Micro-USB charging capability sold separately⁵
POWER MANAGEMENT ¹¹	<ul style="list-style-type: none"> Consumption approx, 13W^{12,13} Warm swap battery
SECURITY FEATURES	<ul style="list-style-type: none"> ARM® TrustZone® (Built-in)
WARRANTY	<ul style="list-style-type: none"> 1-year limited warranty, parts and labor
DIMENSIONS & WEIGHT ^{14,15}	<ul style="list-style-type: none"> 7.6" x 5.2" x 0.5" (without barcode reader section) Approx. 0.93 lb. with Standard Battery



KEY FEATURES	<ul style="list-style-type: none"> Optional 1D/2D barcode reader (SE4710) with LED light – option for portrait or landscape options in SKU configuration
ACCESSORIES	<ul style="list-style-type: none"> Single Bay Desktop USB I/O and charge cradle with 5v power supply and AC cord FZ-VEH1L1AAM 5-Bay Desktop Ethernet I/O and charging cradle with 110W power supply and AC cord FZ-VEH5L1AAM 5-Bay Desktop charge-only cradle with 110W power supply and AC cord FZ-VCH5L1AAM 5-Bay battery charger with 110W power supply and AC cord FZ-VCBT131M Standard Battery 3,200mAh FZ-VZSUT10U Standard battery 3,200mAh – 10 Pack FZ-VZSUT1AU USB Charger⁵ FZ-AAE184EM Rotating Portrait (barcode configured) Hand Strap FZ-VSTL13U Rotating Landscape (barcode configured) Hand Strap FZ-VSTL12U Rotating Hand Strap (No barcode configuration) FZ-VSTL11U Passive Stylus Pen CF-VNP021U Tethers -3 Pack FZ-VNNT11U Screen protector films – 10 Pack FZ-VPFL11U

Please consult your reseller or Panasonic representative before purchasing. Specifications given herein may be changed at any time without prior notice.

¹ 1 MB = 1,048,576 bytes, 1 GB = 1,073,741,824 bytes

² Operation has been tested and confirmed using the following Panasonic brand memory cards: SD (up to 2 GB), SDHC (up to 32 GB), SDXC (up to 64 GB). Compatibility with other SD devices is not guaranteed.

³ Does not guarantee operation of all USB-compatible peripherals.

⁴ 25°C (77°F) environment. Temperature range for charging: 10°C to 35°C (50°F to 95°F) Humidity: 30% to 80% relative humidity.

⁵ The AC adaptor is designed for use with power sources that supply up to 240 V AC.

⁶ Actual performance varies depending on usage conditions, connected peripherals, etc. Typically, operating time is reduced in colder environments.

⁷ Talk time may vary depending on the condition of the mobile network.

⁸ As defined by the JEITA Specification, Working Mode B. (Two times reading in every 10 seconds)

⁹ Enterprise user profile: Barcode usage of 3 scans per minute; WWAN data transfer usage of 90 seconds every 10 minutes; Wi-Fi usage of 30 minutes.

¹⁰ Charging with optional cradle. Varies depending on usage conditions.

¹¹ Need to turn on battery warm swap mode before remove the battery. You can turn on battery warm swap mode by UI operation or FZ-L1 automatically turns into battery warm swap mode when the battery is removed.

¹² When the battery is fully charged (or not being charged) and the unit is off.

¹³ Powered with optional cradle. Rated power consumption.

¹⁴ Actual size may vary by unit configuration.

¹⁵ Average weight. Actual weight may vary by unit configuration.

¹⁶ Do not expose the skin to this product when using the product in a hot or cold environment. When using the product in hot or cold environments, some peripherals may not perform properly. Confirm the recommended operation environment of the peripherals. Using the product continuously hot environments will shorten the product life. Avoid continuous use in these types of environments. When using the product in cold environments, the product may take longer to start up and battery operation time may be reduced. Even when using the product within the temperature and humidity ranges listed here, using the product continuously in extreme environments will result in product deterioration and will shorten the life of the product.

¹⁷ Product functionality cannot be guaranteed if the operating system is modified or replaced by the user or a third party.

800-373-5353
salesmanager@cdce.com
Business Hours: (PST) M-F 8:00 AM – 5:00 PM

